

# Declaration of performance

No. 002-004

1. Identification code  
**best wood MULTITHERM 110**
2. Application  
**Thermal insulation of buildings**
3. Manufacturer  
**Holzwerk Gebr. Schneider GmbH,  
Kappel 28  
88436 Eberhardzell**
4. Authorized person  
**Not relevant**
5. System for assessment and verification of the constancy of performance  
**System 3**
6. Harmonised standard  
**EN 13171:2012+A1:2015**  
Notified body  
**MPA Stuttgart 0672**
7. Declared performances

Essential characteristics	Performance		Harmonised technical specification
Thermal resistance	Thermal resistance	RD Table 1	EN 13171:2012 +A1:2015
	Thermal conductivity	$\lambda_D$ 0.038 W/m*K	
	Thickness	Table 1	
	Thickness tolerance class	T5	
Reaction to fire	Reaction to fire	E	
Durability of reaction to fire under the influence of heat, weather, ageing/degradation	Durability characteristics	NPD	
Durability of thermal resistance under the influence of heat, weather, ageing/degradation	Thermal resistance	RD Table 1	
	Thermal conductivity	$\lambda_D$ 0.038 W/m*K	
	Durability characteristics	NPD	
	Dimensional stability	NPD	
Compression strength	Compressive stress	CS(10/Y)50	
	Point load	NPD	

Tensile / bending strength	Tensile strength perpendicular to the plane of the board	TR10	
	Tensile strength parallel to the plane of the board	NPD	
Durability of compression strength under the influence of ageing/degradation	Creep behaviour under compressive stress	NPD	
Water permeability	Short time water absorption	WS 1	
Water vapor permeability	Water vapor transmission	MU3	
Impact sound transmission (for floors)	Dynamic stiffness	NPD	
	Thickness	NPD	
	Compressibility	NPD	
	Flow resistance	NPD	
Acoustic absorption level	Acoustic absorption	NPD	
Airborne sound insulation level	Flow resistance	AFr50	
Release of hazardous substances, emission into building interior	Release of hazardous substances	NPD	
Smouldering behaviour	Smouldering behaviour	NPD	
NPD: No performance determined			

Table 1

Thickness [mm]	40	60	80	100	120	140	160	180	200	220	240
Thermal resistance $R_D [(m^2 \cdot K)/W]$	1.05	1.55	2.10	2.60	3.15	3.65	4.20	4.70	5.25	5.75	6.30

8. The performance of the above product fulfils the declared performance. The above mentioned manufacturer has the sole responsibility for the preparation of the declaration of performance in accordance with the regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

**Ferdinand Schneider**  
Managing director  
Eberhardzell, 30/08/2025

