

Declaration of performance

No. 015-004

1. Identification code

best wood WALL 180

2. Application

Thermal insulation of buildings

3. Manufacturer

Holzwerk Gebr. Schneider GmbH,

Kappel 28

88436 Eberhardzell

- 4. Authorized person
 - Not relevant
- 5. System for assessment and verification of the constancy of performance

System 3

6. Harmonised standard

EN 13171:2012+A1:2015

Notified body

MPA Stuttgart 0672

7. Declared performances

Essential characteristics	Performance		Harmonised technical specification	
Thermal resistance	Thermal resistance	RD Table 1		
	Thermal conductivity	λ_D 0.043 W/m*K		
	Thickness	Table 1		
	Thickness tolerance class	T5		
Reaction to fire	Reaction to fire	E		
Durability of reaction to fire under the influence of heat, weather, ageing/degradation	Durability characteristics	NPD		
Durability of thermal	Thermal resistance	RD Table 1	EN 13171:2012	
resistance under the	Thermal conductivity	λ _D 0.043 W/m*K	+A1:2015	
influence of heat, weather, ageing/degradation	Durability characteristics	NPD		
	Dimensional stability	DS(70,-)3		
Compression strength	Compressive stress	CS(10/Y)150		
_	Point load	NPD		
Tensile / bending strength	Tensile strength perpendicular to the plane of the board	TR30		



	1	1
	Tensile strength parallel to the plane of the board	NPD
Durability of compression strength under the influence of ageing/degradation	Creep behaviour under compressive stress	NPD
Water permeability	Short time water absorption	WS 1
Water vapor permeability	Water vapor transmission	MU3
Impact sound transmission	Dynamic stiffness	NPD
(for floors)	Thickness	NPD
	Compressibility	NPD
	Flow resistance	NPD
Acoustic absorption level	Acoustic absorption	NPD
Airborne sound insulation level	Flow resistance	AFr100
Release of hazardous substances, emission into building interior	Release of hazardous substances	NPD
Smouldering behaviour	Smouldering behaviour	NPD
NPD: No performance determi	ned	

Table 1

Thickness [mm]	20	40	60	80	100	120	140	160
Thermal resistance	0.45	0.90	1.40	1.85	2.30	2.75	3.25	3.70
R_D [(m ² *K)/W]								

8. The performance of the above product fulfils the declared performance. The above mentioned manufacturer has the sole responsibility for the preparation of the declaration of performance in accordance with the regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Ferdinand Schneider Managing director Eberhardzell, 30/08/2025