

Lifting systems

SIHGA PICK LIFTING SYSTEM for up to 20,000 load cycles

Minimum wood thickness: with planar lifting ≥ 80 mm, with frontal lifting ≥ 90 mm

Item no.	Designation	PU	UP
6205SIHGAPICK	2 x Sihga Pick lifting aid in transport case, without drill bit	1 case	case
6205SIHGAPICK-BOHRUNGEN	Drill hole SIHGA PICK	1 piece	piece




WÜRTH LIFTING SYSTEM

Minimum wood thickness: with planar lifting ≥ 120 mm, with frontal lifting ≥ 160 mm (with locking screw)

The transport anchoring screw is installed countersunk in the element by approx. 10 mm using bit insert AW40.

Item no.	Designation	PU	UP
6206TRANSPORTANKER	Transportation anchor	2 pieces	2 pieces
6203SCHRAUBE12x100/60	Transportation anchor screw 12x100/60	50 pieces/pack	pack
6203SCHRAUBE12x120/100	Transportation anchor screw 12x120/100	50 pieces/pack	pack
6203SCHRAUBE12x160/145	Transportation anchor screw 12x160/145	50 pieces/pack	pack
6204BITEINSATZ	Bit insert AW40 mm	1 piece	piece
6204WÜRTH-BOHRUNGEN	Drill hole Würth lifting systems	1 piece	piece




Soundproofing

best wood HONEYCOMB 30/60

best wood HONEYCOMB is a honeycomb board made from cardboard which prevents movement and sliding of the best wood FILLINGS. A layer thickness with a consistent height is guaranteed by sanding the honeycomb.

Item no.	Designation	PU	UP
6221WABE30	best wood HONEYCOMB 30	1.5 m ² /board, 30 boards/pallet	m ²
6221WABE60	best wood HONEYCOMB 60	1.5 m ² /board, 15 boards/pallet	m ²



best wood FILLINGS

best wood FILLINGS consist of a grain made from natural calcium carbonate, which is manufactured using state-of-the-art grinding and drying systems and sieving machines. It is used for putting into the best wood CLT BOX – CEILING FS and as ballast in best wood ceiling elements.

Item no.	Designation	PU	UP
6220SCHUETTUNG	best wood FILLINGS	25 kg/bag, 40 bags/pallet	bag

Delivery of best wood FILLINGS in Big Bags by request.



SILENT FLOOR EVO insulating mat

SILENT FLOOR EVO is an insulating material made from recycled Latex and foam material. One roll is sufficient for 15 m² and is the perfect enhancement for soundproofing.

Item no.	Thickness	Roll length	Roll width	Roll weight	PU
6225SILENTFLOOR	10 mm	10 m	1.5 m	16.5 kg	15 m ² /roll, 6 rolls/pallet



Accessories for ceiling finishing

Please pay attention to the installation guidelines for small corrections to ceiling finishing!
read more at www.schneider-holz.com

Correction kit

Correction kit "to go" in a practical bag containing all of the tools for repairs to ceilings with a best wood color finish. The correction kit includes: 1 soft wax spatula, 1 manual sanding block, 5 abrasive strips with grain 240, 1 mini paint spray gun, 2 soft wax sticks (in color of your choice).

Item no.	Designation	PU	UP
6215SETFARBLOS	Correction kit colorless	1 piece	piece
6215SETUVPROTECT	Correction kit UV protect	1 piece	piece
6215SETZARTWEISS	Correction kit soft white	1 piece	piece
6215SETEDELWEISS	Correction kit alpine white	1 piece	piece
6215SETLICHTGRAU	Correction kit light grey	1 piece	piece
6215SETKIESELGRAU	Correction kit pebble grey	1 piece	piece
6215SETSANDGELB	Correction kit sand yellow	1 piece	piece
6215SETLACHSROT	Correction kit salmon red	1 piece	piece
6215SETMINTGRUEN	Correction kit mint green	1 piece	piece
6215SETGRAUBLAU	Correction kit grey-blue	1 piece	piece

Information on processing can be found at www.schneider-holz.com/downloads



Soft wax

Soft wax for surface correction of the best wood painted ceilings for repairing scratches, cracks, holes and dents in the surface area. Coordinated with the best wood color variants.

Item no.	Designation	PU	UP
6213WACHSFARBLOS	Soft wax colorless	2 pcs./pack	pack
6213WACHSUVPROTECT	Soft wax UV protect	2 pcs./pack	pack
6213WACHSZARTWEISS	Soft wax soft white	2 pcs./pack	pack
6213WACHSEDELWEISS	Soft wax alpine white	2 pcs./pack	pack
6213WACHSLICHTGRAU	Soft wax light grey	2 pcs./pack	pack
6213WACHSKIESELGRAU	Soft wax pebble grey	2 pcs./pack	pack
6213WACHSGRAUBLAU	Soft wax grey-blue	2 pcs./pack	pack
6213WACHSSANDGELB	Soft wax sand yellow	2 pcs./pack	pack
6213WACHSMINTGRUEN	Soft wax mint green	2 pcs./pack	pack
6213WACHSLACHSROT	Soft wax salmon red	2 pcs./pack	pack



Soft wax spatula

Soft wax spatula for applying and modelling soft wax during surface correction.

Item no.	Designation	PU	UP
6214WACHSSPACHTEL	Soft wax spatula	1 piece	piece



Abrasive strips and manual sanding block

Manual sanding block with Velcro fastener for abrasive strip 70 mm x 125 mm / grain 240 for removing surface soiling from best wood color finished ceilings.

Item no.	Designation	PU	UP
6212GITTER240	Abrasive strips with grain 240	5 pcs./pack	pack
6211HANDSCHLEIFER	Manual sanding block	1 piece	piece



Mini paint spray gun

Mini paint spray gun for correcting and restoring small areas of the best wood color finished ceilings. The nozzle size is 0.8 mm; container capacity 125 ml.

Item no.	Designation	PU	UP
6216PISTOLEMINI	Mini paint spray gun	1 piece	piece



Large paint spray gun

Large paint spray gun for coating additional components such as purlins or posts. The nozzle size is 1.4 mm; container capacity 500 ml.

Item no.	Designation	PU	UP
6216PISTOLEGROSS	Large paint spray gun	1 piece	piece



Paint roller for UV protect

Foam material roller for coating additional components such as purlins or posts with UV protect. Roll available in 110 mm and 160 mm. The bracket for the foam material roller must be purchased separately.

Item no.	Designation	PU	UP
6217ROLLE110	Paint roller 110	10 pcs./pack	pack
6217ROLLE160	Paint roller 160	10 pcs./pack	pack



Paint bracket for UV protect

Paint bracket for paint roller. Available in sizes 100 mm and 150 mm.

Item no.	Designation	PU	UP
6218BUEGEL10	Bracket 100 for paint roller	1 piece	piece
6218BUEGEL15	Bracket 150 for paint roller	1 piece	piece

Paint brush

Paint brush for painting additional components such as purlins and posts.
The paint brush is available in sizes 50 mm and 100 mm.


Item no.	Designation	PU	UP
6219PINSEL50	Paint brush 50	1 piece	piece
6219PINSEL100	Paint brush 100	1 piece	piece



best wood CEILING TAPE

Ceiling tape for masking all best wood painted ceilings.
The ceiling tape is available with a width of 50 mm. 50 running metres per roll.

Item no.	Designation	PU	UP
6210DECKENTAPE	best wood ceiling tape	50 lfm/roll	roll



SOLITEX® ADHERO

Full-surface self-adhesive airtightness and weathering-protection membrane

Application

Allows airtightness to be created on wood-based products and mineral substrates – e.g. on the exterior side of unplastered (fair-faced) masonry or concrete components with joints.

Thanks to its full-surface adhesion, the membrane provides temporary protection for intermediate ceilings and floors on multi-storey CLT (cross-laminated timber) or wooden-frame buildings during the construction period. It also protects wall elements and roof structures with a roof pitch of greater than 14° for a period of up to 3 months.

In addition, it fulfils the requirements of the Central Association of the German Roofing Trade (ZVDH) for temporary coverings on roofs for the specified time period.

Advantages

Protects the structure: Diffusion-permeable and maximum protection against driving rain; keeps building components dry by means of a pore-free moisture-active functional membrane; easy and reliable installation thanks to its split release film; sticks immediately to substrates with sufficient load-bearing capacity; permanent protection thanks to the high resistance to ageing and heat of the TEEE membrane; 3 months of outdoor exposure



developed and produced by pro clima

Protection and cover fleece	Polypropylene microfiber
Membrane	Monolithic TEEE
Thickness	0.70 ± 0.05 mm
s _d -value	0.40 ± 0.08 m
Fire behaviour	E
Outdoor weather exposure	3 months
Water column	10.000 mm
Surface weight beneath membrane	240 ± 5 g/m ²
Temperature resistance	-40 °C bis +100 °C
Tensile strength longitudinal/transverse	250 ± 30 N/5 cm / 200 ± 30 N/5 cm

Item no.	Roll length	Roll width	Area	Roll weight
6224SOLITEXADHERO	30 m	1.50 m	45 m ² /roll	12 kg

Colors for processing at home

Lignosil®-Inco-DL base color

Lignosil®-Inco-DL dilution as the basis for independent mixing of appropriate color shades with our mixing concentrate paint or for applying the soft white color shade. Instructions mixing ratios for processing yourself can be found at www.schneider-holz.com/downloads.



Item no.	Designation	PU	UP
6208FlascheGrundfarbe	Lignosil®-Inco-DL dilution	1 l bottle	litre
6208EimerGrundfarbe	Lignosil®-Inco-DL dilution	5 l bucket	litre

Paint mixing concentrate

Paint mixing concentrate is available in all of our best wood color shades, and must be mixed with Lignosil®-Inco-DL dilution. Instructions mixing ratios for processing yourself can be found at www.schneider-holz.com/downloads. **The following colors are available: alpine white, light grey, pebble grey, grey-blue, sand yellow, mint green, salmon red.**



Item no.	Designation	PU	UP
6208Flasche100	Paint mixing concentrate - any color available	100 ml bottle	litre
6208Flasche500	Paint mixing concentrate - any color available	500 ml bottle	litre
6208Flasche1000	Paint mixing concentrate - any color available	1 l bottle	litre

UV protect

The transparent UV protect glaze variant protects the light color of the spruce, and is also suitable for independent application. Installation guidelines can be found at www.schneider-holz.com/downloads.



Item no.	Designation	PU	UP
6208FlascheUVProtect	UV protect	1 l bottle	litre
6208EimerUVProtect	UV protect	5 l bucket	litre

Connector

X-fix C

X-fix C is a two-piece, self-tightening wood-wood connector for compression and tension-proof connection of CLT ceilings and walls. X-fix C is a wedge-shaped dovetail wood-wood connector. The X-fix C wedge shape even clamps large-format ceiling panels or wall parts in a self-tightening, form-fitting way.

The advantages of X-fix C: Fast installation, form-fitting connection is ideal for visible surfaces, no panel tighteners required for ceiling connections, and thanks to the wedge shape, X-fix C even clamps large-format ceiling panels together in a self-tightening way, no metal in the pure wood-wood connection.



Item no.	Designation	PU	UP
6209X-FIX	X-fix C 96/130/90	1 piece	piece
6209X-FIX-BOHRUNGEN	Drill hole for X-fix (both sides)	1 piece	piece

Lighting systems



LED 130 round

The lighting systems are coordinated with our best wood GLULAM and CLT ceilings and CLT BOX, and can be supplied ready-drilled with the relevant holes at an additional cost.

Even light distribution over the entire light outlet surface.
Dimmable with a trailing edge dimmer.

The lights are only suitable for indoors and for connecting to safety extra-low voltage.

Item no.	Designation	PU	UP
6222LED130RWEISS	LED 130 round white	1 pc.	piece
6222LED130RTITAN	LED 130 round matt titanium	1 pc.	piece
6222LED130R-BOHRUNGEN	Drill holes for LED 130	1 pc.	piece



Wattage [Watt]	11
Lamp	SMD-LED
Energy efficiency classes	A++-A
Light color	Warm white
Color temperature [Kelvin]	Approx. 3000 K
Luminous flux [Lumen]	840 lm
Color rendering	Ra > 80
Material	Aluminum/PMMA diffusor disk
Light outlet opening	130 mm Ø
Service life	50,000 hours
Operating device (transformer)	Included (packaged separately)
Dimmable	Yes
Installation depth	55 mm with best wood ceiling systems

LED 150 square

The lighting systems are coordinated with our best wood GLULAM and CLT ceilings and CLT BOX, and can be supplied ready-drilled with the relevant holes at an additional cost.

Even light distribution over the entire light outlet surface.
Dimmable with a trailing edge dimmer.

The lights are only suitable for indoors and for connecting to safety extra-low voltage.

Item no.	Designation	PU	UP
6222LED150QWEISS	LED 150 square white	1 pc.	piece
6222LED150QTITAN	LED 150 square matt titanium	1 pc.	piece
6222LED150Q-BOHRUNGEN	Drill holes for LED 150	1 pc.	piece



Wattage [Watt]	10
Lamp	SMD-LED
Energy efficiency classes	A++-A
Light color	Warm white
Color temperature [Kelvin]	Approx. 3000 K
Luminous flux [Lumen]	870 lm
Color rendering	Ra > 80
Material	Aluminum/PMMA diffusor disk
Light outlet opening	150x150 mm
Service life	50,000 hours
Operating device (transformer)	Included (packaged separately)
Dimmable	Yes
Installation depth	55 mm with best wood ceiling systems

LED 68 spot

The lighting systems are coordinated with our best wood GLULAM and CLT ceilings and CLT BOX, and can be supplied ready-drilled with the relevant holes at an additional cost.

The reflector is made from real glass, and the lighting system is dimmable with a trailing edge dimmer.

The lights are only suitable for indoors and for connecting to safety extra-low voltage.

Item no.	Bezeichnung	PU	UP
6222LED68SPOTWEISS	LED 68 spot white	1 pc.	piece
6222LED68SPOTTITAN	LED 68 spot nickel brushed	1 pc.	piece
6222LED68SPOT-BOHRUNGEN	Drill holes for LED 68 spot	1 pc.	piece



Wattage [Watt]	8
Lamp	COB LED
Energy efficiency classes	A++-A
Light color	Warm white
Color temperature [Kelvin]	Approx. 3000 K
Luminous flux [Lumen]	850 lm
Color rendering	Ra > 90
Material	Diecast aluminum/real glass reflector
Light outlet opening	45 mm Ø
Radiation angle, swivelling	38 degrees
Service life	50,000 hours
Operating device (transformer)	Included (packed with spot)
Dimmable	Yes
Installation depth	55 mm with best wood ceiling systems