

Fastening material

best wood Ejothem STR U 2G screw-in anchor for insulation boards

Pre-assembled screw-in anchor, Ø 8 mm, for insulation boards.
Universal screw-in anchor for countersunk and surface fixed installation in concrete and masonry. Anchor plate Ø 60 mm.



Item no.	Delivery form	PU	UP	
6121DSD060115	Anchor length 115 mm	100 pc/pack	pack	
6121DSD060135	Anchor length 135 mm	100 pc/pack	pack	
6121DSD060155	Anchor length 155 mm	100 pc/pack	pack	
6121DSD060175	Anchor length 175 mm	100 pc/pack	pack	
6121DSD060195	Anchor length 195 mm	100 pc/pack	pack	
6121DSD060215	Anchor length 215 mm	100 pc/pack	pack	
6121DSD060235	Anchor length 235 mm	100 pc/pack	pack	
6121DSD060255	Anchor length 255 mm	100 pc/pack	pack	
6121DSD060275	Anchor length 275 mm	100 pc/pack	pack	
6121DSD060295	Anchor length 295 mm	100 pc/pack	pack	
6122STRSTEPS	Polystyrene caps (EPS) have to be ordered separately	500 pc/pack	pack	

Only available in full packing units (packs)

**The anchors need to be anchored in a sufficient depth in the substrate.
The effective embedment depth of the insulation board anchors for different service categories is as follows:**

Use category A-D ≥ 25 mm

- A: Standard concrete and concrete facing layers
- B: Bricks, solid bricks, concrete solid bricks and lightweight concrete solid bricks
- C: Vertically perforated bricks, perforated calcium-silicate bricks and lightweight concrete hollow blocks
- D: Lightweight aggregate concrete with open structure

Use category E ≥ 65 mm

- E: Porous concrete (e.g. Ytong)

Note

UV exposure from sunlight on unprotected anchor: ≤ 6 weeks