

Bonding and sealing

TESCON INVIS

Black multi-purpose adhesive tape

Application

Outside: Windproofing of sarking membranes, roof lining membranes and wall lining membranes (e.g. with pro clima SOLITEX FRONTA WA and SOLITEX FRONTA QUATTRO). Wind-proof bonding of wood-based panels used as sarking boards. Airtight bonding of roof-mounted vapour check and refurbishment vapour check and airtightness membranes.

Inside: Airtight bonding of vapour check and airtightness membranes as well as airtight wood-based panels.

All bonds - indoor and outdoor - can be made between the same materials as well as with adjacent structural components with a smooth, non-mineral surface (e.g. pipe penetrations, roof windows).

Advantages

All-round adhesive tape for internal and external use, 6 months outdoor exposure; easily torn off by hand with a soft fleece backing; suitable for sealing to penetrations; also used for a windtight adhesion of wall lining membranes behind suspended facades; waterproof adhesive.



developed and produced by pro clima

Backing	Special PP fleece
Separating layer	Siliconized paper
Temperature resistance	Long-term - 40°C to + 90°C
Processing temperature	Above - 10°C
Outdoor weather exposure	6 months

Item no.	Roll length	Roll width	Delivery form	KG / PU		
6102TESCONINVIS	30 m	60 mm	1 box (10 rolls)	7.0 kg		
			1 roll	0.7 kg		